


Nickel Cadmium Batteries High Capacity Rapid Charge

Model: PS-AAXF


Specifications

| | | |
|---|-------------------------|-----------------|
| Nominal Voltage | | 1.2 Volt |
| Rated Capacity | | 700 mAh |
| Dimensions | Diameter in. (mm) | 0.56 (14.1) |
| | Height in. (mm) | 1.93 (49.0) |
| | Height with solder tabs | 1.97 (50.0) |
| | Weight Approx. | 22 gm |
| | Internal Resistance | <40mΩ |
| | Standard Charge (0.1C) | 70 mA |
| | Trickle Charge | (0.03C)~(0.05C) |
| | Fast Charge ΔV | 700 mA |
| Recommended Operating Temperature Range | Std/Trickle Charge | 20±5°C |
| | Fast Charge | 20±5°C |
| | Discharge | 20±5°C |
| | Storage | -20°C to 45°C |
| Standard Discharge (0.2C) Cut Off Voltage | | 1.0V per cell |
| High Rate Discharge (1 C) Cut Off Voltage | | 1.0V per cell |


Dimensions




Charging and Discharging Characteristics




Discharge



Standard Charge




Fast Charge



Trickle Charge



▲ Standard Battery Cycle Life ▲




▲ Fast Charging Cycle Life ▲




▲ Cycle Life Using Trickle Charging ▲



▲ Stand-by Battery Life ▲



▲ Capacity vs. Temperature ▲



▲ Retained Capacity In Storage ▲

Corporate Headquarters and Domestic Sales
 Power-Sonic Corporation • 7550 Panasonic Way • San Diego, CA 92154 • U.S.A
 Phone: (619) 661-2020 • Fax: (619) 661.3650
 Email Sales: national-sales@power-sonic.com
 Email Customer Service: customer-service@power-sonic.com
 E-mail Technical Support: technical-support@power-sonic.com

International Sales
 Power-Sonic Corporation • P.O. Box 5242 • Redwood City, CA 94063 • U.S.A.
 Phone: (650) 364-5001 • Fax: (650) 366-3662
 Email Sales: international-sales.com@power-sonic.com

www.power-sonic.com