



## PS-632 6 Volt 3.5 AH

### Rechargeable Sealed Lead Acid Battery

We've Got The Power.™




### Features


- Absorbent Glass Mat (AGM) technology for superior performance
- Valve regulated, spill proof construction allows safe operation in any position
- Power/volume ratio yielding unrivaled energy density
- Rugged impact resistant ABS case and cover (UL94-HB)
- Approved for transport by air. D.O.T., I.A.T.A., F.A.A. and C.A.B. certified
- U.L. recognized under file number MH 20845

### Terminals: (mm)

- F1 - Quick disconnect tabs, 0.187" x 0.032"- Mate with AMP. INC. FASTON "187" series



### Physical Dimensions: in (mm)



**L:** 2.60 (66) **W:** 1.30 (33) **H:** 4.65 (118) **HT:** 4.80 (122)

Tolerances are +/- 0.04 in. (+/- 1mm) and +/- 0.08 in. (+/- 2mm) for height dimensions. All data subject to change without notice.

### Performance Specifications

**Nominal Voltage** ..... 6 volts (3 cells)

#### Nominal Capacity

20-hr. (175mA to 5.25 volts) .....	3.50 AH
10-hr. (330mA to 5.25 volts) .....	3.30 AH
5-hr. (590mA to 5.10 volts) .....	2.95 AH
1-hr. (2.17A to 4.50 volts) .....	2.17 AH
15-min. (6.86A to 4.50 volts) .....	1.72 AH

**Approximate Weight** ..... 1.37 lbs. (0.62 kg)

**Energy Density (20-hr. rate)** ..... 1.34 W-h/in<sup>3</sup> (81.54 W-h/l)

**Specific Energy (20-hr. rate)** ..... 15.33 W-h/lb (33.79 W-h/kg)

**Internal Resistance (approx.)** ..... 28 milliohms

**Max Discharge Current (7 Min.)** ..... 10.5 amperes

**Max Short-Duration Discharge Current (10 Sec.)** ..... 35.0 amperes

#### Shelf Life (% of nominal capacity at 68°F (20°C))

1 Month .....	97%
3 Months .....	91%
6 Months .....	83%

#### Operating Temperature Range


Charge ..... -4°F (-20°C) to 122°F (50°C)

Discharge ..... -40°F (-40°C) to 140°F (60°C)


**Case**..... ABS Plastic

**Power-Sonic Chargers** ..... PSC-6500A-C


**Shelf Life & Storage**




**Discharge Characteristics**




**Discharge Time vs. Discharge Current**



**Life Characteristics in Stand-By Use**



**Life Characteristics in Cyclic Use**



**Charging**

**Cycle Applications:** Limit initial current to 1.35A. Charge until battery voltage (under charge) reaches 7.20 to 7.35 volts at 68°F (20°C). Hold at 7.20 to 7.35 volts until current drops to under 45mA. Battery is fully charged under these conditions, and charger should be disconnected or switched to "float" voltage.

**"Float" or "Stand-By" Service:** Hold battery across constant voltage source of 6.75 to 6.90 volts continuously. When held at this voltage, the battery will seek its own current level and maintain itself in a fully charged condition.

**Note:** Due to the self-discharge characteristics of this type of battery, it is imperative that they be charged within 6 months of storage, otherwise permanent loss of capacity might occur as a result of sulfation.

**Chargers**

Power-Sonic offers a wide range of chargers suitable for batteries up to 100AH. Please refer to the Charger Selection Guide in our specification sheets for "C-Series Switch Mode Chargers" and "Transformer Type A and F Series". Please contact our Technical department for advice if you have difficulty in locating suitable models.

**Further Information**

Please refer to our website [www.power-sonic.com](http://www.power-sonic.com) for a complete range of useful downloads, such as product catalogs, material safety data sheets (MSDS), ISO certification, etc..

**Contact Information**

DOMESTIC SALES  
Tel: +1-619-661-2020  
Fax: +1-619-661-3650  
national-sales@power-sonic.com

CUSTOMER SERVICE  
Tel: +1-619-661-2030  
Fax: +1-619-661-3648  
customer-service@power-sonic.com

TECHNICAL SUPPORT  
Tel: +1-619-661-2020  
Fax: +1-619-661-3648  
support@power-sonic.com

INTERNATIONAL SALES  
Tel: +1-650-364-5001  
Fax: +1-650-366-3662  
international-sales@power-sonic.com