



Intertek

# PSC-124000ACX 12V 4A

Sealed Lead Acid Battery Charger  
ACX Battery Charger Series


## FEATURES

- Universal input voltage range 90VAC - 240VAC
- Automatic, current sensing dual-rate charging for efficient, care-free and safe operation
- LED indicators
- Alligator clip connectors with insulated sleeves

## APPROVALS

- Approved for transport by air. D.O.T., I.A.T.A., F.A.A. and C.A.B. certified
- ISO9001:2015 – Quality management systems
- ETL
- DOE
- FCC
- CE

## CHARGER CHARACTERISTICS



### GLOBAL HEADQUARTERS (USA AND INTERNATIONAL EXCLUDING EMEA)

**Power-Sonic Corporation**  
365 Cabela Dr Suite 300,  
Reno, Nevada 89439  
USA  
T: +1 775 824 6500  
E: customer-service@power-sonic.com

### POWER-SONIC EMEA (EMEA – EUROPE, MIDDLE EAST AND AFRICA)

Smitspol 4, 3861 RS Nijkerk,  
The Netherlands  
T NL: + 31 33 7410 700  
T UK: + 44 1268 560 686  
T FR: + 33 344 32 18 17  
E: salesEMEA@power-sonic.com

## PERFORMANCE SPECIFICATIONS

### Input Specs

AC input voltage rating	100Vac-240Vac
AC input frequency rating	50Hz-60Hz
AC input voltage range	90Vac-240Vac
AC input frequency range	47Hz-63Hz
AC input current	1.1A@115Vac/0.65A@230Vac
AC input power	75W
AC static state current	50mA

### Output Specs

Output voltage range	4-15.0Vdc
Output current	4A@12Vdc
Output power	60W
Bulk charge current rating	4A
Bulk charge voltage rating	14.7Vdc
Float charge voltage rating	13.2Vdc
Light switching current	800mA
Charging capacity range	14Ah to 55Ah

### General Specs

Efficiency	80%
Over load protection	<6A
Short circuit protection	Yes
Reversed polarity connectors protection	Yes
Operating temperature	0°C-40°C
Storage temperature	-30°C-85°C
Net weight	500g
Dimensions	155*71*47
Enclosure	Plastic Case
Application	Indoor
Charger type	Desktop

### Safety Specs

Withstand voltage (Hi-Pot)	3000Vac ≤ 10mA (3s)
Insulation resistance	>100MΩ @500Vdc
Safety standard	ETL/CE
Compliance	FCC

### LED Indicator Status

Green - Float charge	Green Flash - Power on and empty load
Red - Bulk charge	Red Flash - Short or reversed polarity

## INPUT PLUGS & OUTPUT

Part Number	Input Plug	Output Connection
PSC124000ACX-US	NEMA-A	Alligator Clips
PSC124000ACX-EU	CEE-C	Alligator Clips
PSC124000ACX-UK	BS-G	Alligator Clips

## FURTHER INFORMATION

Please refer to our website [www.power-sonic.com](http://www.power-sonic.com) for a complete range of useful downloads, such as product catalogs, safety data sheets, ISO certification, etc.